

# HSF RoHS

REV	ECN NO	DESCRIPTION	DATE	NAME
A		NEW		

### Specifications

1. Current Rating: 3Amps
2. Contact Resistance: 20mΩ
3. Insulator Resistance: 1000 Megohms min.
4. Dielectric withstanding Voltage: AC/DC 1000V
5. Operating Temperature: -40℃ to +105℃
6. Contact Material: Copper alloy
7. Insulator Material: As follows
8. Plated: As follows

### Ordering Information

L308 XX -XX 8 X X XX X

Insulation Height*Wide (H*W) Option: 50=5.0*5.2 71=7.5*5.0 85=8.5*5.0	NO. of Pins Per Row: 1-40P	Insulation Material Option: 1=PBT 2=PPS 3=NY6T 4=LCP 5=NY66 6=Customized 7=NY46 8=NY9T	Contact Plating 0=0.8" Gold 1=Au1" Gold 2=Au1.5" Gold 3=Au2" Gold 4=Au3" Gold 5=Au5" Gold 6=Customized 7=Gold/Tin 8=Tin	Serial NO. 01-69 (No pillars) 70-89 (pillars) 90-99 (outside pillars)	Packing A=PE Bag B=Tube C=Tray D=Reel
---	-------------------------------	---	--	--	---

Dimension antitheses list

ITEM	PC	H	W
Standard	3.0	5.0/7.1/8.5	5.0/5.2
Alternate			

**LDCONN 东莞连大精密制品有限公司**  
**连大 DongGuan LianDa Precision Products Co., LTD**

TITLE	PH2.54mm 2XNP Dual row Female Header centipede feet type	DRAWN BY	Lujunhui	18.04.03
PART NO	L308XX-XX8XXXXX	CHECKED BY		
DRAWING NO		APPROVED BY		
SCALE	1:1	UNIT	mm	PAGE 1/1
				SIZE A4

STANDARD TOLERANCE (EXCEPT SPECIFIED)			
LINER		ANGLES	
.0	±0.30	0.°	±3°
.00	±0.20	.0°	±2°
.000	±0.10	.00°	±1°

PCB LAYOUT

