

# HSF RoHS

REV	ECN NO	DESCRIPTION	DATE	NAME
A		NEW		




### Specifications

- 1.Current Rating:2.0Amps
- 2.Insulation Resistance:1000 MΩ min.
- 3.Dielectric withstanding Voltage: 500V AC/DC
- 4.Contact Resistance:20 mΩ max.
- 5.Operating Temperature:-40℃ to+105℃
- 6.Contact Material: Brass
- 7.Insulation Material:Asfollows,UL94V-0,Black
- 8.Plated: Au Over Ni


### Ordering Information

L231 XX -XX 1 X X XX X

Insulation Height*Wide (H*W) 5.7*5.5	Per Row: Insulation Material Option: 10P 26P 30P 40P 44P	Contact Plating 0=0.8" Gold 1=Au1" Gold 2=Au1.5" Gold 3=Au2" Gold 4=Au3" Gold 5=Au5" Gold 6=Customized 7=Gold/Tin 8=Tin	Serial NO. 01-69	A、袋装 B、管装 C、盘装 D、卷装
---	--	--	---------------------	------------------------------



Dimension antitheses list				
ITEM	PC	PB	H	Pin Length
Standard	2.80	9.30	5.7	8.20
Alternate				



PCB LAYOUT

STANDARD TOLERANCE (EXCEPT SPECIFIED)	
LINER	ANGLES
.0 ±0.30	0.° ±3°
.00 ±0.20	.0° ±2°
.000 ±0.10	.00° ±1°

**LDCONN 东莞连大精密制品有限公司**  
 连大 DongGuan LianDa Precision Products Co., LTD

TITLE	PH2.00mm Pin Header Dual Row 90°	DRAWN BY	YTT	16.02.03
PART NO	L231XX-XX1XXXXX	CHECKED BY		
DRAWING NO		APPROVED BY		
SCALE	1:1	UNIT	mm	
PAGE	1/1	SIZE	A4	